

Category6 Cross Connect System

Mounting Panel

100 and 200 pair 110-type panel for interconnection wiring
Mounting: Rack / Wall Mounting
Color: white

Connection Block

Housing: PC/ABS
PIN: phosphor-bronze with gold plating
Standard: Category6
Types: 4 Pair / 5 Pair
Color: white

Connection Clip

Housing: PC/ABS
Cover: transparent PC
PIN: phosphor-bronze with gold plating

Patch Cord

Cable

Conductor: 7 copper wires $\varnothing 0.20$ mm (0.008"), 24 AWG
Diameter of insulated conductor: 0.98 ± 0.05 mm ($0.039" \pm 0.002"$)
Number of pairs: 1/2/4
Color of twisted pairs: blue-white/blue, orange-white/orange, green-white/green, brown-white/brown
Jacket: PVC $\varnothing 2.6 \pm 0.2$ mm ($0.1" \pm 0.008"$)/PVC $\varnothing 4.2 \pm 0.2$ mm ($0.17" \pm 0.008"$)/PVC $\varnothing 5.5 \pm 0.2$ mm ($0.22" \pm 0.008"$)
Jacket color: light grey

Plug

1 Piece 8P8C
1 or 2 pieces, 1 or 2 or 4-pair 110 type, for stranded (patch) cable
Material: Poly Carbonate (PC)
PIN: Phosphor bronze with gold plating

Ordering Information

X06S- R-050	i-Net Networks Cross Connect System Category6 Rack Mount 100Pair 110 Type
R	R —Rack Mount, W —Wall Mount without Leg, L —Wall Mount with Leg
050	050 —50 Pair, 100 —100 Pair, 200 —200 Pair
X06M- W	i-Net Networks Cross Connect Cable Manager Wall Mount
W	W —Wall Mount, R —Rack Mount
X06B- 4	i-Net Networks Cross Connection Block Category6 4Pair
4	4 —4 Pair, 5 —5 Pair
X06C- 1	i-Net Networks Cross Connection Clip Category6 1Pair
1	1 —1 Pair, 2 —2 Pair, 4 —4 Pair
X06P- 1-3	i-Net Networks Cross Connect Patch Cord Category6 Stranded 24AWG 1Pair Milky Grey 3 Feet
1	1 —1 Pair, 2 —2 Pair, 4 —4 Pair
3	03 —3 Feet, 06 —6 Feet, 10 —10 Feet