

Category7 SSTP Solid Indoor Cable

Specifications

Meets ISO/IEC 11801 & IEC 61156-5, category 7 requirements
 Low Smoke Zero Halogen
 The cable meets UL VW-1, IEC 60332-1, CM fire safety standard

Description

Shielded Copper cable, 4 pairs, Category 7, Solid, 600MHz
 4 separately foil-shielded pairs
 General shield: wire braid
 Cable is used for indoor installation

Materials

Conductive material: Soft annealed electrolytic copper
 Conductor insulation: HDPE, film-porous-film structure
 The cable jacket: LSZH
 Shield: Separately shielded pairs with polyester aluminum foil
 General shield: tin Copper braid – 60% minimum

Technical Characteristics

Conductor diameter: 0.64 mm (0.025") (22 AWG)
 Outer cable diameter: 8.2 mm (0.32")
 Operating temperature: -30°C – +70°C (-22°F – +158°F)
 Weight per 1000 ft (304.8 m): 21.3 kg (47.7 lbs)
 Standard package: 305m (1000 ft), 500 m (1640 ft)

Electrical Characteristics

Frequency , MHz	Pair Attenuation, dB/100m	NEXT losses, dB	RL, dB
4	3.6 (1.10)	85	24
10	5.8 (1.80)	85	27
16	7.4 (2.26)	85	27
20	8.3 (2.53)	85	27
31.25	10.4 (3.2)	85	25
62.5	14.6 (4.45)	85	23
100	18.4 (5.61)	85	23
200	26.2 (7.98)	83	20
300	32.1 (9.78)	80	20
600	49 (14.93)	80	20

Conductor resistance at 20°C (68°F)	80.0 Ohm/km (128.75 Ohm/mile)
DC Resistance Unbalance	2% max
Resistance at frequency 1-600 MHz	100 ± 15 Ohm
Transfer impedance at frequency 1-10 MHz	5 MOhm/m (1.52 MOhm/ft) max
Capacitive unbalance at frequency 1 kHz	1.2 pF/m (0.36 pF/ft) max
Maximum voltage	60 V RMS
Dielectric rigidity	700 V/min
Insulation resistance at 20°C (68°F)	152 MOhm/km (244.62 MOhm/mile) min
Propagation velocity	79-80%
Max propagation delay at frequency 1 MHz	5.3 ns/m (1.61 ns/ft)
Max propagation delay at frequency 10 MHz	5.0 ns/m (1.52 ns/ft)
Max propagation delay at frequency 100-600 MHz	5.0 ns/m (1.52 ns/ft)
Max derivation of propagation delay at frequency 1-600 MHz	15 ns/100 m (4.57 ns/100 ft)

Ordering Information

HI7SSL-M i-Net Networks Horizontal Indoor Cable Category7 SSTP Solid 22AWG 4 Pair LSZH Milky Gray

M—Milky Gray, **B**—Blue, **L**—Black, **G**—Green, **R**—Red, **Y**—Yellow

