

Floor Standing Cabinet

Feature

- Easy to assemble flat pack or fully assembled
- Connected by four-corner to ensure the intensity
- Exquisite design with precise craftsmanship
- Toughened glass or vented front door
- Adjustable feet and heavy duty castors
- Top and bottom panel for cable entry
- Removable side panel
- High-density vented rear door

Standard

ANSI/EIA RS-310-D, IEC297-2, DIN41491 part 1, DIN41494
 Height: 15U, 18U, 22U, 27U, 32U, 37U, 42U, 47U
 Width: 600mm and 800mm
 Depth: 600mm, 800mm, 1000mm
 Package: Assembled/Unassembled

Material

Frame: Steel
 Others: SPCC cold rolled steel
 Thickness: Profile - 0.08" (2.0 mm), Angle - 0.06" (1.5 mm),
 Side Panel - 0.03" (0.8 mm), others - 0.05" (1.2 mm)

Loading Capacity

Static loading: up to 400kg (15U~27U), up to 800kg (32U~47U)

Surface Finish

Black, Degreasing, pickling, phosphoric, powder coated

Ordering Information

CFG-**15-6060** i-Net Networks Floor Cabinet Black Front Glass Door 15U 600x600mm
 CFM-**15-6060** i-Net Networks Floor Cabinet Black Front Perforated Metal Door 15U 600x600mm
15 **15**—15U, **18**—18U, **22**—22U, **27**—27U, **32**—32U, **37**—37U, **42**—42U, **47**—47U
6060 **6060**—600x600mm, **6080**—600x800mm, **601K**—600x1000mm, **8080**—800x800mm, **801K**—800x1000mm



Main Structure

Front glass (FGD) or vented (FPMD) door
 Quick open side door (QOSD)
 Four adjustable profile (4AP)
 Two vertical cable manager (CAWM-V-C x 2)
 Light duty castor (LDC) (15-22U), Heavy duty castor (HDC) (27-47U)
 Twenty five cage nut (CACN-1 x 25)
 Four top mounted fans (4F)
 Lock with key (CAL-SD)
 Adjustable stopper feet (SF)