

Fiber Optic Adapter

Description

- Terminated with metal stopper and screws
- Polymeric caps protect the adapters against dust
- Allows easy identification
- Singlemode adapters come with white (FC) and blue (SC) caps
- Multimode adapters come with black (FC) and beige (SC) caps
- FC, SC, ST adapters are inline and they are used for the precise centre positioning of connectors' ferrules in special sleeves
- Centre positioning in MTRJ adapters is performed using guiding pins and the ferrules are centre positioned in special sleeves

Material

Nickel brass, plastic
Phosphor bronze centre sleeve

Technical Specification

Insertion loss: 0.3 dB
Storage temperature: -40°C to +80°C (-40°F to +176°F)
Operating temperature: -20°C to +70°C (-4°F to +158°F)
Maximum permissible humidity: 95%

Ordering Information

AS-**M-TT** i-Net Networks Fiber Optic Simplex Adapter Multimode ST-ST
AD-**M-TT** i-Net Networks Fiber Optic Duplex Adapter Multimode ST-ST
M **M**—Multimode, **S**—Singlemode
TT **TT**—ST-ST, **CC**—SC-SC, **LL**—LC-LC, **FF**—FC-FC, **MM**—MTRJ-MTRJ, **TC**—ST-SC, **CL**—SC-LC, **LF**—LC-FC

