

Fiber Optic Patch Cord

Description

IEC 60874-10, TIA/EIA-604-2, Telcordia GR-326-CORE
Meets IEC 60332-1 fire safety standard



Specification

Ferrule Outer Diameter	1.25mm, 2.5mm ($\pm 0.0005\text{mm}$), 125~125.5, 126~127			
Cord	SM	9/125 μ	Ferrule	Zirconia
	MM	50/125 μ , 62.5/125 μ	Spring	Stainless Steel
	Type	ST, SC, LC, FC, MTRJ	C-ring	SK5M
Connector	Boot Color	Yellow, Blue, Black, Green, Beige	Ring	Brass
	Hood	0.9mm, 2.0mm, 2.4mm, 3.0mm	Crimping ring	Aluminum
	Insertion Loss	SM: <0.3 dB, MM: <0.4 dB	Boot	Kay Flex
Technical Characteristics	Return Loss	> 45 dB	Dust cap	PE (Black, White, Yellow)
	End Face Radius	10 mm <R< 25 mm (0.39"<R<0.98")	Coupling Device	PBT
	Apex Offset	< 0.002" (50 μm)	Frame	PBT
	Operating Temperature	-40°C to +85°C (-40°F to 185°F)	Washer	-
	Length	1m (3.28ft), 2m (6.56ft), 3m (9.84ft), 5m (16.4ft), 10m (32.8ft)	Cable	LSZH

Ordering Information

PCD50P- TT-01	i-Net Networks Fiber Patch Cord Duplex Multimode 50/125 μ PC ST-ST 1m
PCD62P- TT-01	i-Net Networks Fiber Patch Cord Duplex Multimode 62.5/125 μ PC ST-ST 1m
PCD09P- TT-01	i-Net Networks Fiber Patch Cord Duplex Singlemode 9/125 μ PC ST-ST 1m
PCD50A- TT-01	i-Net Networks Fiber Patch Cord Duplex Multimode 50/125 μ APC ST-ST 1m
PCD62A- TT-01	i-Net Networks Fiber Patch Cord Duplex Multimode 62.5/125 μ APC ST-ST 1m
PCD09A- TT-01	i-Net Networks Fiber Patch Cord Duplex Singlemode 9/125 μ APC ST-ST 1m

TT—ST-ST, **TC**—ST-SC, **TL**—ST-LC, **TF**—ST-FC, **TM**—ST-MTRJ

CC—SC-SC, **CL**—SC-LC, **CF**—SC-FC, **CM**—SC-MTRJ

TT **LL**—LC-LC, **LF**—LC-FC, **LM**—LC-MTRJ

FF—FC-FC, **FM**—FC-MTRJ

MM—MTRJ-MTRJ

01 **01**—1meter, **02**—2meter, **03**—3meter, **05**—5meter, **10**—10meter