

Fiber Optic Pigtail

Description

Compliant with Telcordia, TIA/EIA/IEC
Meets IEC 60332-1 fire safety standard



Specification

Ferrule Outer Diameter	SM	125~125.5	Ferrule	Zirconia Ceramic
	MM	126~127	Spring	Stainless Steel
Cord	SM	9/125μ	C-ring	SK5M
	MM	50/125μ, 62.5/125μ	Ring	Brass
Connector	Type	ST, SC, LC, FC	Crimping ring	Aluminum
	Boot Color	Yellow, Black	Materials	Boot
Technical Characteristics	Insertion Loss	SM < 0.3 dB, MM < 0.4 dB	Dust cap	LD PE
	Return Loss	> 45 dB,	Coupling Device	Brass
	End Face Radius	10 mm < R < 25 mm	Frame	PBT
Length	Apex Offset	< 50 mm	Washer	Brass
		1m (3.28ft), 2m (6.56ft), 3m (9.84ft)	Cable	LSZH

Ordering Information

- PTS50P-**T-1** i-Net Networks Fiber Pigtail Simplex Multimode 50/125μ PC ST 1m
- PTS62P-**T-1** i-Net Networks Fiber Pigtail Simplex Multimode 62.5/125μ PC ST 1m
- PTS09P-**T-1** i-Net Networks Fiber Pigtail Simplex Singlemode 9/125μ PC ST 1m
- PTS50A-**T-1** i-Net Networks Fiber Pigtail Simplex Multimode 50/125μ APC ST 1m
- PTS62A-**T-1** i-Net Networks Fiber Pigtail Simplex Multimode 62.5/125μ APC ST 1m
- PTS09A-**T-1** i-Net Networks Fiber Pigtail Simplex Singlemode 9/125μ APC ST 1m

T —ST, **C**—SC, **L**—LC, **F**—FC, **M**—MTRJ

1 —1meter, **2**—2meter, **3**—3meter